



7.5 kg 75 kg

- Digital veicelle dedikert til høyhastighets veieprosesskontroll
- Lastecelle laget av rustfritt stål, hermetisk forseglet IP69K
- skala Plattformstørrelse opp til 400 x 400 mm
- Veiekapasiteter 7,5, 15, 30, 75 kg
- Oppløsning på opptil 500 000 pts
- Delesertifikat av NAWI (OIML R76) og AWI (OIML R51 og R61) for modellene 15, 30 og 75 kg
- Integreerte veiefunksjoner: Høyhastighetssender, fylling, dosering ved lossing
- Programmerbare digitale filtre
- 2 digitale innganger og 4 digitale utganger
- Feltbusversjon: port RS485 Modbus og port CANOPen
- Ethernet-versjon: EtherNet/IP, Profinet, Webserver



English Description

7.5 kg 75 kg

- Digital load cell dedicated to high speed weighing process control
- Load cell made of stainless steel, hermetically sealed **IP69K**
- Max. scale Platform size up to 400 x 400 mm
- Weighing capacities 7.5, 15, 30, 75 kg
- Resolution up to 500 000 pts
- Part certificate of NAWI (OIML R76) and AWI (OIML R51 and R61) for models 15, 30 and 75 kg
- Integrated weighing functions: **High speed transmitter, filling, dosing by unloading**
- Programmable digital filters
- 2 digital inputs and 4 digital outputs
- Fieldbus version: port **RS485 Modbus** and port **CANOpen**

- Ethernet version: **EtherNet/IP, Profinet, Web server**

Category: [Scaime](#), [Veieceller](#)

Lager status / Stock Status: instock